



Determination of 11 cannabinoids in Industrial Hemp using \$14,990 HPLC from CTInstruments

Accurate determination of cannabinoids in industrial hemp is important from regulatory compliance point of view to meet the permissible 0.3% THC limit. We present an easy-to-use, accurate, reliable, and affordable HPLC for measuring 11 cannabinoids in a variety of samples. This application note describes analysis of industrial hemp.

HPLC Features

Reciprocating Pump

UV/VIS Detector

• Rheodyne 7725i Injector

 Temperature-controlled Column Compartment

• CTI HPLC Software

HPLC Specifications

Flow Rate 0.001 - 5mL/min

Max Pressure 6,300 psi
Flow Accuracy ≤±1%

Flow Precision RSD < 0.1%

Qualitative Repeatability RSD ≤0.2% (Naphthalene/

Methanol standards)

Quantitative Repeatability RSD ≤0.5% (Naphthalene/

Methanol standards)

Wavelength Range 180 - 680nm

Spectrum Bandwidth 8nm
Wavelength Accuracy ±1nm

Wavelength Precision Below 0.1nm

Noise ≤0.25X10⁻⁵AU

HPLC Column Specifications

Column TypeC18, SS bodyDimensions150x4.6mmPacking5μm particles

Guard Column C18



2020 COMMERCIAL CANNABIS AWARDS WINNER



Best Cannabinoids
Potency Testing
Solutions Manufacturer North America

cannabishplcanalyzer.com

Calgary, AB T2P 3Y6 Canada

CTInstruments Ltd. is ASTM International Organizational Member (www.astm.org)
CTInstruments Ltd. is a member of ASTM Committee D37 on Cannabis



Biomass Sample

Sample Type	Industrial Hemp Flower		
Strain	NBS Auto Flower		
Condition	Dry		



PROCESS

1. Extraction

Extraction of cannabinoids from dried industrial hemp is the initial step in the analysis.

Extraction Parameters

Sample Weight 500mg

Sample Preparation Grinding/Homogenization

Extraction Solvent Methanol

Extraction Conditions 15 minutes at room temperature

Dilution In acetonitrile

2. Injection and HPLC Analysis

After the extraction is completed, diluted extract is injected into HPLC for analysis.


Chromatographic Conditions

Mode Isocratic
Temperature 30°C

Detection UV at 220nm

Mobile Phase Buffer: Acetonitrile

Flow Rate 1.2mL/min








3. Report Generation

After the analysis is completed, CTI HPLC software auto-processes the chromatogram, followed by export to custom lab report generation program in MS Excel (highly customizable and automated report generation for ease of use).



Lower Limit of Quantification (LLOQ)

The lower limit of quantification (LLOQ) is the lowest amount of a cannabinoid in a sample that can be quantitatively determined with suitable precision and accuracy using the corresponding method and dilution rates. All values below this threshold are reported as NR - None Reported.

Compound		LLOQ (%, w/w)
THCV	Tetrahydrocannabivarin	0.01
Δ8-THC	(-)-Δ8-THC	0.01
Δ9-THC	(-)-Δ9-THC	0.01
Δ9-THCA-A	(-)-trans-Δ9-THC acid A	0.01
CBD	Cannabidiol	0.01
CBDA	Cannabidiolic acid	0.01
CBDV	Cannabidivarin	0.01
CBG	Cannabigerol	0.01
CBGA	Cannabigerolic acid	0.01
CBN	Cannabinol	0.01
CBC	(+/-) Cannabichromene	0.01

Instrument Calibration & Quality Control

Date of Quality Control	Standard	Standard Concentration (ug/mL)	Measured Concentration (ug/mL)	Delta (%)	PASS/FAIL	Notes	
27-Mar-21	Benzoic acid	1002.9	1004.0	0.1%	PASS		
27-Mar-21	CBD	100.5	99.7	-0.8%	PASS		

Web: cannabishplcanalyzer.com

Email: support@cannabistestingsimplified.com

Tel: +1 (403) 629-8597